1		30	With particular dielectric
1	LIQUID CRYSTAL SYSTEM	30	mirror for spatial light
2	Liquid crystal for recording or		modulator (i.e., SLM)
	imaging on photosensitive	31	Electron beam excitation
_	medium	32	.Plasma excitation
3	Printer or print bar		
4	Exposure device for lithography	33	.Electrical excitation of liquid
5	.Projector including liquid		crystal (i.e., particular
	crystal cell (s)		voltage pulses, AC vs. DC,
6	Overhead projector	2.4	threshold voltages, etc.)
7	Video/motion picture projector	34	With application of holding or
8	Plural light path projectors		bias voltage (i.e., voltage
9	Having light separated into S		which does not change the
	and P polarization		optical state of the liquid
10	Wherein liquid crystal cells	2.5	crystal)
	include microencapsulated or	35	For driving Grandjean to focal
	polymer dispersed liquid		conic or dynamic scattering
	crystal	2.5	type liquid crystal
11	.Heads-up display	36	Including diverse driving
12	.Liquid crystal writing tablet	0.7	frequencies
13	.Liquid crystal eyewear (glasses,	37	Polarity based driving
	goggles, etc.)	38	With supplemental capacitor
14	For protection	39	In active matrix with separate
15	.Stereoscopic		dedicated capacitor line
16	.Liquid crystal window	40	With antistatic elements
17	.Computational system employing	41	With particular switching
1 /	liquid crystal element (neural		device
	network, correlation device,	42	Transistor
	optical computer)	43	Structure of transistor
18	.Variable or rotatable retarder	44	With light block
10	used with other retarders to		conductively connected to
	produce filtering effects		transistor
	(Solc, Lyot, Partial)	45	Transferred transistor
19	PARTICULAR EXCITATION OF LIQUID	46	With particular gate
	CRYSTAL		electrode structure
20	.Thermal excitation	47	With gate electrode between
21	By heating electrode		liquid crystal and
22	By light beam heating (e.g.,		semiconductor layer
	IR, laser, etc.)	48	Plural nonredundant
23	.Magnetic or pressure excitation		transistors per pixel
24	Optical excitation	49	Two terminal nonlinear
25	With photoconductive layer		switching device (e.g., N-I-N,
23	(e.g., spatial light		S-I-S, Ferroelectric, etc.)
	modulator(SLMs))	50	Diode
26	Of an alloy of S, Se, or Te	51	Metal-insulator-metal (i.e.,
27	With silicon photoconductive		MIM)
27	layer	52	With particular insulating
28	With silicon photodiode, N-I-		layer
20	N photoconductor structure, or	53	Varistor
	P-I-P photoconductor structure	54	Matrix including additional
29	With particular light blocking		element (s) which correct or
۵)	layer for separating read and		compensate for electrical
	write lights		fault
		55	Laser links
		56	PARTICULAR STRUCTURE

57	<pre>.Lens or prism separate from projection system (i.e., it is not integral part of illumination system)</pre>	80	With color formed by different color polarizer or color filter associated with each cell
58	.Holder, support, frame, or housing	81	With cells being substantially identical and driven
59	Including electromagnetic shielding		simultaneously, providing improved contrast
60	Including resilient support member	82	With projection of electrodes in one cell substantially
61	.Particular illumination		nonoverlapping that of another
62	With integral optical element for guiding or distributing		<pre>cell (i.e., for improving resolution)</pre>
	light from the light source	83	With each cell displaying a
63	Specifically for guiding light		different pattern
	in a front-lit device	84	.Having significant detail of
64	Diffuser between light source		cell structure only
	and liquid crystal	85	Producing a greyscale effect
65	Edge lit type light guide behind liquid crystal	86	Microencapsulated or polymer dispersed liquid crystal
66	Louvres	87	For variable polarizer
67	Reflector having particular	88	Polymer network liquid crystal
	shape behind light source	89	With particular encapsulating
68	With plural diverse light		medium
	sources (e.g., for day and night)	90	With second material between liquid crystal and
69	Electroluminescent light source		encapsulating medium
70	Fluorescent light source	91	With nonpolymer encapsulating
71	Formed of planar phosphor or		medium
	fluorescent layer separate	92	Formed by particular technique
	from illumination source	93	Having UV polymerized element
72	.Detector of liquid crystal	94	Formed with particular
	temperature		alignment technique
73	.Interconnection of plural cells	95	Microlenses
	in parallel (e.g., edge to	96	Polarizer
	edge)	97	Color
74	.Interconnection of plural cells	98	Circular
	in series	99	With particular non-zero angle
75	For compensation of birefringence effects		between polarization axis and orientation direction
76	Of twisted (or chiral) nematic or supertwisted nematic liquid	100	For ferroelectric liquid crystal
	crystal	101	For supertwisted nematic
77	With particular cooperation		liquid crystal
	between cells (e.g.,	102	With particular non-zero angle
	alternating selection or		between polarization axis and
	simultaneous selection of		compensator optical axis
	cells)	103	With particular non-zero and
78	Cell cooperation providing		non-90 angle between opposite
	multicolor display		polarization axes
79	With color formed by	104	Filter
	different dye in each cell	105	Interference filter
		106	Color filter

107	With different liquid crystal thickness for each color of	129	With plural alignments on the same substrate
	filter	130	For perpendicular alignment
108	With plural colors for each	131	Silanes
	display element (i.e., each	132	For parallel alignment
	pixel or segment)	133	With chiral smectic liquid
109	With unequal areas for	133	crystal (includes
200	different colors or with		ferroelectric liquid crystal)
	fractional shift between one	134	
	line of colors and the next	134	With particular pretilt
110			angle from the alignment layer
	Opaque mask or black mask	135	With particular polymer
111	Conductive mask		composition of the alignment
112	Diffuser (on viewer side of		layer (e.g., fluorine-
	liquid crystal)		containing aliphatic
113	Reflector		polyamide)
114	Dielectric mirror (i.e., in	136	With particular pretilt
	devices excited other than by		angle (i.e., with liquid
	photoconductive layer) or		crystal other than chiral
	transflector		smectic)
115	Cholesteric reflector	137	Antireflection layer
116	Photoconductive element (i.e.,	138	Insulating layer
	not used for exciting)	139	Electrode or bus detail (i.e.,
117	Compensator or retarder (i.e.,		excluding supplemental
 ,	not using liquid crystal cell)		capacitor and transistor
118	With refractive indices in the		electrodes)
110		140	Formed of semiconductor
110	x, y, and z directions	140	material
119	Multiple compensators	1 4 1	
120	Including at least one with	141	Interdigited (comb-shaped)
	negative intrinsic		electrodes
	birefringence	142	Segmented or fixed pattern
121	With particular non-zero angle	143	Matrix electrodes
	between compensator optical	144	Split pixels
	axis and orientation direction	145	Nonrectilinear rows and
122	Particular nonoptical film or		columns
	layer (e.g., adhesive layer,	146	Nonrectangular (odd) shaped
	barrier layer)		pixels
123	Alignment layer	147	Multilayer electrodes
124	Formed by particular	148	Resistance reducing
	technique (e.g., Langmuir		electrodes
	Blodgett, stretching, etc.)	149	Having connection detail to
125	Having particular deposited	117	external circuit
	structure (e.g., angled,	150	Featuring flexible circuit
	plural layered) produced by	130	
	vapor deposition		(i.e., tape automated bonding
126	Having structure produced by	1 - 1	(TAB), etc.)
120	rubbing under particular	151	With driving circuit having
			input and output electrodes on
	rubbing conditions (e.g.,		liquid crystal substrate
	particular direction, rubbing force, by using named rubbing	152	With detail of terminals to
			external circuit
1 0 7	material or roller, etc.)	153	Liquid crystal seal
127	<pre>material or roller, etc.)Formed of a liquid crystal</pre>	153 154	
	<pre>material or roller, etc.)Formed of a liquid crystal material</pre>		Liquid crystal seal
127 128	<pre>material or roller, etc.)Formed of a liquid crystal</pre>		Liquid crystal sealWith particular injection port

156	Formed as walls (e.g., between	185	.In cholesteric phase
	pixels) or integral with substrate	186	.In nematic phase
157	Plural types in single liquid	187	NOMINAL MANUFACTURING METHODS OR POST MANUFACTURING PROCESSING
158	crystal cellSubstrate	188	OF LIQUID CRYSTAL CELL
150		189	.Changing liquid crystal phase
160	Fiberoptic faceplateWith particular topology	190	.Injecting liquid crystal .Sealing of liquid crystal
100	(i.e., other than for	191	.Sealing of liquid crystal .Aligning liquid crystal with
	diffraction and spacers)	191	means other than alignment
161	Heating or cooling element		layer
101	other than for exciting	192	.Defect correction or
162	Dual function layer or element	172	compensation
163	Nonchiral additive in the	193	LIQUID CRYSTAL OPTICAL ELEMENT
	liquid crystal material	194	.Passive liquid crystal polarizer
164	Fluorescent additive	195	.Antidazzle mirror formed from
165	Pleochroic dye		liquid crystal cell
166	Nonspacer particles	196	.Beam dividing switch formed from
	significantly smaller than		liquid crystal cell
	liquid crystal thickness	197	Including passive liquid
	(e.g., scattering centers,		crystal switch portion
	ferromagnetic particles, etc.)	198	.Liquid crystal etalon
167	WITH SPECIFIED NONCHEMICAL	199	.Liquid crystal sensors (e.g.,
	CHARACTERISTIC OF LIQUID		voltmeters, pressure sensors,
1.00	CRYSTAL MATERIAL		temperature sensors)
168	.Utilizing change between diverse phases (e.g., cholesteric to	200	.Liquid crystal lenses other than for eyewear
1.60	nematic)	201	.Liquid crystal diffraction
169	.Utilizing change within liquid		element
	<pre>crystal phase (e.g., Grandjean to focal conic, etc.)</pre>	202	For beam steering
170	.Utilizing reversal in sign of dielectric anisotropy		
171	.Within smectic phase	EODETCN	ART COLLECTIONS
172	Within chiral smectic phase (includes ferroelectric)	FOREIGN	AKI COMMECTIONS
173	Greyscale resulting from	FOR	CLASS-RELATED FOREIGN DOCUMENTS
175	liquid crystal property other		UTILIZING A LIQUID CRYSTAL
	than solely Smectic A		MATERIAL (359/36)
174	Antiferroelectric	FOR 100	.With particular illumination
175	.Within cholesteric phase	EOD 101	(359/48)
176	Using reflection characteristic	FOR 101	Having optical element (e.g.,
177	.Within nematic phase		curved reflector behind light source, etc.) (359/49)
178	Negative dielectric anisotropy only	FOR 102	Fluorescent light (e.g., FLAD
179	Twisted (or chiral) nematic or supertwisted nematic	FOR 103	type) (359/50) .Microencapsulated liquid crystal
180	Having particular parameter of	EOD 104	(359/51)
181	twistHaving particular	FOR 104	eWith particular encapsulating medium (359/52)
TOT	birefringence or retardation		.Plural contiguous cells (359/53)
182	CELL CONTAINING LIQUID CRYSTAL OF	FOR 106	.Having electrodes arranged into rows and columns (359/54)
183	SPECIFIC COMPOSITION .Polymer liquid crystal	FOR 107	With liquid crystal electrode
184	.In smectic phase		excitation (359/55)
TOI	. III BINECCIC PHASE		

- FOR 108 ...For ferroelectric liquid crystal (359/56)
- FOR 109 ...With particular switching device (359/57)
- FOR 110 ..With particular switching device (359/58)
- FOR 111 ...Transistor (359/59)
- FOR 112 ...Diode (359/60)
- FOR 113 .Having particular nonelectrical detail of cell structure enclosing or adjacent liquid crystal material (359/62)
- FOR 114 .. Polarizer (359/63)
- FOR 115 ...Color (359/64)
- FOR 116 ...Circular (359/65)
- FOR 117 ..Diffuser (359/69)
- FOR 118 ...Dielectric mirror or transflector (359/71)
- FOR 119 ..Particular nonoptical film or layer (e.g., adhesive layer, barrier layer, etc.) (359/74)
- FOR 120 ... Alignment layer (359/75)
- FOR 121Formed by particular technique (e.g., vapor deposition, rubbing, etc.) (359/76)
- FOR 122For perpendicular alignment (359/77)
- FOR 123For parallel alignment (359/ 78)
- FOR 124 ... Substrate (359/82)
- FOR 125 ..Holder, support, or frame (359/83)
- FOR 126 .With specified electrode excitation characteristic of liquid crystal material (359/84)
- FOR 127 ..Provided by particular circuit (359/85)
- FOR 128 .With detector of liquid crystal temperature (359/86)
- FOR 129 .Electrode detail (359/87)
- FOR 130 .. Reversal in sign of dielectric anisotropy (359/92)
- FOR 131 .Birefringers effect (359/93)
- FOR 132 .Variable index of refraction (359/94)
- FOR 133 .Variable diffraction (359/95)
- FOR 134 .Variable absorption of light due to an additive in the liquid crystal material (359/96)
- FOR 135 .. Flurescent additive (359/97)
- FOR 136 .. Pleochroic dye (359/98)

- FOR 137 .With specified nonchemical characteristic of liquid crystal material (359/99)
- FOR 138 .. Within smectic phase (359/100)
- FOR 139 ..Within cholestric phase (359/
- FOR 140 .. Within nematic phase (359/102)
- FOR 141 .Cell containing liquid crystal of specified composition (359/ 103)
- FOR 142 .. In smectic phase (359/104)
- FOR 143 .. In cholesteric phase (359/105)
- FOR 144 .. In nematic phase (359/106)